

Onity's *ADVANCE* Trillium RFID lock features a stylish new look in a two-piece modular design, with a low-profile reader designed for today's modern aesthetics.

### Advanced Credential Security

Trillium RFID locks include the option to use MIFARE® Plus Technology, and enhanced credential security for RFID cards. Trillium locks also are available with a DirectKey™ module option, enabling a proven mobile key solution.

### Easy Upgrade Path

The *ADVANCE* Trillium RFID lock provides an easy upgrade path where Onity *ADVANCE* series locks currently are installed, no new door cuts or repainting are required. Properties with Onity *ADVANCE* locks can update to *ADVANCE* Trillium RFID by installing a new reader and control board.

### Electronic Features

- Compatible with Onity HT22, OnPoint and HT24W electronic locking systems
- Reading technology: contactless RFID (ISO14443A, 14443B part 4, NFC)
- Supports MIFARE Classic, MIFARE Plus, MIFARE Ultralight and MIFARE Ultralight C cards
- Multiple opening devices available: cards, wristbands, keychains, etc.
- Non-volatile memory: records last 500 openings including date, time and card user
- DirectKey-ready: Bluetooth® module can be shipped on-board or added later
- Programmable to customer needs ("Office Mode", free passage, etc.)
- LEDs indicate lock status including low battery
- Programmable for length of time door remains open and automatic closing
- Each new guest card overrides any previous ones preventing re-entry
- Masterkeying available
- Capability to manage staff shifts


### Physical Features

- Off-line installation (no wires required)
- "Do-Not-Disturb" Function (thumbturn)
- Corrosion resistant
- Finishes: Satin Chrome, Polished Chrome, Satin Brass, Antique Brass, Polished Brass, Satin Nickel and Dark Bronze
- Handles: Wing, Barcelona, Toledo, Granada, Jerez



### Specifications

- Size:
- Temperature tolerance ranges:
  - Alkaline batteries: -18°C to 55°C
  - For non-fire rated doors only, lithium batteries: -40°C to 75°C
- Humidity: up to 95% non-condensing
- Power supply: 4 alkaline AA batteries (included), with 2 years life approx.



### Certifications

- EC Certificate of Conformity under EN 14846\*
- European Fire Certification EN 1634-1
- Directive 2014/30/EU (Electromagnetic Compatibility)
- Directive 2014/53/EU (R&TTE)
- DIN 18273 Certification
- BHMA 156.25 & BHMA 156.13
- UL10C (3 hours)

\* With EURO 5470H mortise only